

Feature Specifications

Concurrent Users	Unrestricted
Concurrent Connections	128,000
PPP Configurations	5
Tunnels	300
Static Routes	300
Security Policies (each kind)	400
Protocols	255
IP Aliases	300
IP Pass-through Hosts	300
Address Objects	600
Time Group Objects	100
VPN Security Associations	600
VPN Users (maximum non-concurrent)	750
Mobile VPN Users (maximum concurrent)	300
GTA Mobile VPN Client Licenses	1
VLANS	300

Hardware Design

The GB-2000e chassis is a 1-RU rack-mount unit designed to minimize heat buildup with two cooling fans. It has four high speed 10/100 Mbps Ethernet interfaces to ensure high performance and network design flexibility, and two multifunction DB-9 serial interfaces to provide access for a serial console or dial-up modem/ISDN TA. VPN acceleration is performed by a hardware VPN acceleration card. Flash memory stores and runs the pre-installed GB-OS. Power is supplied by a power cable. A reboot may be triggered using the "Reset" pinhole.

Caution

At least 6" should be provided behind the system to allow efficient cooling. Inadequate clearance can cause the system to overheat.

Warning

There are no user serviceable parts in the GB-2000e. Opening the unit will void the warranty on the system, and may cause injury.

I/O Interface Specifications

- Four (4) 10/100 Mbps Ethernet 10Base-T network interfaces on UTP Cat. 3, 4 and 5, and fast Ethernet 100Base-TX network interfaces on UTP Cat. 5. NIC 0 is factory set to IP address 192.168.71.254.
- Two (2) RS-232 (DB-9) serial interfaces. The serial console / modem port should be set to 38,400 bps, 8 bit, 1 stop, no parity and flow control to hardware.
- Two (2) USB ports.

Hardware Specifications

CPU Speed	2.0 GHz Intel Celeron
RAM & Flash Memory	256 MB RAM, 2 GB CF
Standard 10/100 Ethernet NICs	Four (4)
VPN Hardware Acceleration	PCI
Power Supply	One (1)

Physical Specifications

Width x Depth x Height	16.87" x 14.17" x 1.73"
Weight	10.5 lbs (4.76 kg)
Operating Temperature	5-40° C
Humidity	20-90% RH, Non-condensing
AC Input Voltage	100-240 VAC/47-63 Hz
Rack Mountable	1-RU Unit

LED Status Indicators

Front Panel LEDs

Power LED	Lights green when powered up
Disk LED	Blinks red when flash memory is accessed
10/100 LEDs	Lights green for a 100 Mbps connection Unlit for a 10 Mbps connection
Link/Activity LEDs	Lights green for an established connection Blinks green for activity

Supported Software

- GB Commander 2.0 (firewall management)
- GTA Reporting Suite 2.0 (firewall log reporting)

Optional Features

- Mail Sentinel Anti-Spam (email filtering)
- Mail Sentinel Anti-Virus (email filtering)
- Surf Sentinel (web content filtering)
- H₂A - High Availability
- Additional GTA Mobile VPN Client licenses
- Support contracts (including IPS policy updates w/GB-OS 5.0 and above)



- 10/100 Mbps NIC Ports
- DB-9 Serial Interface
- Internal Power Supply
- Two Hardware Cooling Fans
- Two USB Ports
- DB-9 Serial Interface